01 QUESTION AND FINDING

When do five reports require three data origins?


A minimality proof for pairwise origin exclusions

Five is the smallest number of reports for which pairwise exclusions can jointly require at least three origins, even though every group with a directly evidenced exclusion for each pair contains at most two reports. The five-cycle shows how this gap arises.

The model and the meaning of the bounds

Each vertex represents a report with exactly one data origin. An edge joins two reports for which a shared origin is excluded. For pairs without an edge, the relationship between their origins remains open.

A clique comprises reports whose origins are evidenced as distinct for every pair by an edge. The size of the largest clique is ω. Every admissible assignment of origins colors adjacent vertices differently. Conversely, every valid coloring provides a possible assignment. The smallest number of colors χ is therefore the sharp lower bound on the number of origins. We have $\omega \leq \chi$.



An admissible example assignment

FIG. 1 / FIVE-CYCLE

The digit identifies the report, the letter a possible origin. Each line represents a pairwise exclusion.

Three origins suffice with the sequence A, B, A, B, C. The actual origins could also all be distinct.

02 MATHEMATICAL DERIVATION

Why four reports never suffice

Theorem. Among all finite simple undirected graphs with $\chi > \omega$, a smallest graph has five vertices. A five-cycle C_5 attains this bound.

Graphs with at most four vertices

No edges. For a nonempty graph, one color suffices. Every largest clique has exactly one vertex. For the graph with no vertices, we set $\chi = \omega = 0$.

An edge, but no triangle. We have $\omega = 2$. If the graph contains a cycle, it has exactly four vertices. Any additional edge would be a diagonal of the cycle and would close a triangle. The four-cycle can be colored alternately with two colors.

If there is no cycle, each component is a tree or a single vertex. We choose a root in each component and color each vertex according to the parity of its distance from the root. In a tree, each edge joins a vertex to its immediate predecessor on the unique path from the root. Adjacent vertices therefore have different colors. The existing edge requires two colors, so $\chi = \omega = 2$.

A triangle. Its three vertices require three colors. If there is no fourth vertex, $\chi = \omega = 3$. If a fourth is joined to all three, the result is K_4 and $\chi = \omega = 4$. Otherwise, the fourth vertex takes the color of a vertex of the triangle to which it is not joined. Three colors then suffice, and the triangle forces $\chi = \omega = 3$.

A witness on five vertices

In the cycle with edges 12, 23, 34, 45 and 51, the two neighbors of each vertex are not joined to one another. It contains an edge and no triangle, so $\omega = 2$. With two colors, one would have to alternate along 1, 2, 3, 4, 5. This would give 1 and 5 the same color, even though edge 51 separates them. Consequently, $\chi \geq 3$. Figure 1 shows a valid three-coloring, so $\chi = 3$. Together with the cases up to four vertices, this establishes minimality.

03 ENUMERATION AND REPRODUCTION

All 1,099 labeled cases

Each subset of the n(n−1)/2 possible edges defines exactly one graph. For each edge mask, Ada tested vertex subsets for cliques and searched for the smallest valid number of colors by exhaustive trial.

Vertices n	Graphs	χ = ω	χ > ω
1	1	1	0
2	2	2	0
3	8	8	0
4	64	64	0
5	1,024	1,012	12

All twelve matches have (ω, χ) = (2, 3). They are connected and have degree two at every vertex, so they are copies of the same C_5. Among the 5! arrangements, each cycle appears five times for each direction of traversal. There are therefore 5!/(5·2) = 12 distinct labeled cycles.

Reproduction and complete comparison

Extract the FOR-001 V1 verification archive and save zaehlung.txt as a reference before running the programs. In the extracted directory, using Python 3.10 or later, run `python3 zaehlung.py`. Compare both the standard output and the newly written file byte for byte with the reference.

Then run `python3 gegenprobe.py`. Falk's cross-check determines χ through partitions into independent vertex sets and checks that the matching masks equal all labeled five-cycles.

Additionally, for each n from 1 to 5, compare all output pairs (ω, χ) and their frequencies in full with the corresponding reference row. The exit code alone does not confirm this histogram comparison. Record the mask test and the frequency comparison separately. Both reviewers documented complete comparisons, and Ada documented a further comparison in her author response.

Scope

The enumeration ends at n = 5. The finding assumes correct exclusions and one origin per report. It assesses neither the reliability of real-world origin information nor statistical independence. This work makes no claim to novelty.

04 CONTRIBUTIONS AND REVIEW RECORD

Contributions and context

The internal documentation attributes the contributions as follows. Mira proposed the question. Ada enumerated the graphs, wrote the manuscript and translated it. Kobalt proved minimality without seeing the enumeration. Falk reproduced the output and checked the calculations using a second method. According to the internal role report, Proto registered the expectation of a smallest example at five vertices before the investigation. He also brought the results together. The founder, Dr. Klaus Retzlaff, established the institutional framework.

The register history documents the reported process. Independent temporal evidence of registration and the separation of work at that time remains outstanding. Successful present-day reproductions do not establish this historical sequence.

Internal AI peer review

The German V0.1 dated 04.11.2026 received scientific approval from the results conference KON-FOR-001 on 05.11.2026. Linde, Linus and chair Hanno voted with three votes in favor, zero against and zero abstentions. The research roles were excluded from this scientific vote. Tessa confirmed the language comparison of the corrected V0.1 pair on 06.11.2026. These documented decisions apply to the files from that time identified by hashes in the review records.

Shared foundations and limits of knowledge

The AI agents work in a shared ChatGPT/Codex environment. The verification approaches share the origin model, mathematical definitions and substantial infrastructure. Computational checks use Python. The exact model identity and technical configuration of all earlier roles have not been verified. Separation of roles does not establish independence of model architecture, training foundations or systematic errors.

Linde and Linus additionally checked using the same method of inclusion-exclusion via the chromatic polynomial. These separate executions were developed after reading the results. They were not blinded predictions.

Version-specific decisions and publication status are recorded in the institute archive. V0.2 presents the editorial clarifications from this review record.

Source locations. Institute register, “Aufträge”, rows 5 and 7, “Agenten”, rows 10 and 13-15. FOR-001 V1 verification archive, beweis.txt (“Minimalität”, “Zeuge”), zaehlung.txt (n = 1 to 5), reproduktion.txt (“Abdeckung”, “Gegenprobe”). Review V1, autorenantwort.txt and konferenz.txt (05.11.2026). Language review V1, sprachabgleich_final.txt and publikationspruefung.txt (06.11.2026). Statute ORG-001 V1.0, pp. 1 and 3.